

Vodtovsled

Split links


Mallas de encaje

Vare nr. Part no. Parte no.	Str. Size Tamaño	= Ø	SWL 5:1	A	B	Vægt Weight Peso
	mm		Ton	mm	mm	kg/100
DS 10 GA L	3/8"	10	0,1	50	16	8,5
DS 12 GA	1/2"	12	0,2	55	18	16,5
DS 16 GA	5/8"	16	0,3	72	21	33,0
DS 19 GA	3/4"	19	0,5	80	24	50,0
DS 22 GA	7/8"	22	0,6	88	27	75,0
DS 10 SS L	3/8"	10	0,2	50	16	8,5
DS 12 SS	1/2"	13	0,3	55	18	16,5
DS 16 SS	5/8"	16	0,4	72	21	33,0
DS 19 SS	3/4"	19	0,5	80	24	50,0
DS 22 SS	7/8"	22	0,6	88	27	75,0
DS 14 CH	9/16"	14	0,5	60	18	20,0
DS 16 CH	5/8"	16	0,7	72	21	33,0
DS 19 CH	3/4"	19	1,4	80	23	55,0
DS 22 CH	7/8"	22	1,8	88	27	75,0
DS 25 CH	1"	25	2,2	94	35	110,0

*Stål 60, galvaniseret
Steel 60, galvanized
Acero grado 60, galvanizado*

*Rustfrit stål
Stainless steel
Acero inoxidable*

*Chrom stål, gul galvaniseret
Chrome steel, yellow galvanized
Acero cromado,
galvanización amarilla*



Boss vodtovsled

Rustfrit stål

Boss split link

Stainless steel

Mallas de encaje

Boss

Acero inoxidable

Vare nr. Part no. Parte no.	SWL 5:1	A	B	C	Vægt Weight Peso
	Ton	mm	mm	mm	kg
BOSS DL 18 S	0,2	78	45	18	0,17
BOSS DL 19 S	0,4	79	50	24	0,27
BOSS DL 20 S	0,5	82	55	24	0,30
BOSS DL 21 S	1,4	108	63	25	0,70
BOSS DL 22 S	1,3	106	68	33	0,60